

TEHNIČNE SPECIFIKACIJE

TIP 3000

(NOTRANJE OZOBLJENJE)

Št. Načrta:	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
3106.20.20.0-0.0400.00	475	300	55	448	352	16	13,5	12	399	401	46	46	9	9	305	5	61	-2,5	46	33
3108.20.20.0-0.0450.00	531	345	55	500	400	16	15,5	14	449	451	46	46	9	9	350	5	70	-2,5	46	38
3110.20.20.0-0.0560.00	641	450	55	610	510	20	15,5	14	559	561	46	46	9	9	456	6	76	-3,0	46	51
3112.20.20.0-0.0630.00	717	516	55	682	578	20	17,5	16	629	631	46	46	9	9	522	6	87	-3,0	46	59
3114.20.20.0-0.0710.00	797	594	55	762	658	24	17,5	16	709	711	46	46	9	9	600	6	100	-3,0	46	68

Št. Načrta:	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
3116.20.25.0-0.0886.00	980	752	63	944	827	36	17,5	16	885	887	54	54	9	9	760	8	95	-4,0	54	111
3118.20.25.0-0.1077.00	1169	930	63	1134	1017	36	17,5	16	1076	1078	54	54	9	9	940	10	94	-5,0	54	140
3120.20.25.0-0.1180.00	1287	1020	63	1243	1117	36	22	20	1179	1181	60	54	15	9	1030	10	103	-5,0	54	185

Št. Načrta:	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
3130.20.40.0-0.1500.00	1634	1308	94	1582	1418	40	26	24	1498	1501	85	81	13	9	1320	12	110	-6,0	85	410
3132.20.40.0-0.1700.00	1834	1498	94	1782	1618	44	26	24	1698	1701	85	81	13	9	1512	14	108	-7,0	85	475

Št. Načrta:	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
3134.20.50.0-0.1800.00	1971	1554	109	1905	1695	36	33	30	1798	1802	100	99	10	9	1568	14	112	-7,0	100	762
3136.20.50.0-0.2000.00	2171	1764	109	2105	1895	40	33	30	1998	2002	100	99	10	9	1778	14	127	-7,0	100	827
3138.20.50.0-0.2240.00	2411	1984	109	2345	2135	48	33	30	2238	2242	100	99	10	9	2000	16	125	-8,0	100	961
3140.20.50.0-0.2490.00	2661	2240	109	2595	2385	54	33	30	2488	2492	100	99	10	9	2256	16	141	-8,0	100	1053
3142.20.50.0-0.2800.00	2971	2544	109	2905	2695	60	33	30	2798	2802	100	99	10	9	2560	16	160	-8,0	100	1205

TEHNIČNE SPECIFIKACIJE

TIP 3000

(NOTRANJE OZOBLJENJE)

Št. Načrta:	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
3122.20.30.0-0.1120.00	1232	960	79	1188	1052	36	22	20	1118	1121	70	63	16	9	970	10	97	-5,0	70	206
3124.20.30.0-0.1250.00	1362	1090	79	1318	1182	40	22	20	1248	1251	70	63	16	9	1100	10	110	-5,0	70	231
3126.20.30.0-0.1400.00	1512	1224	89	1468	1332	44	22	20	1398	1401	80	63	26	9	1236	12	103	-5,0	80	296
3128.20.30.0-0.1600.00	1712	1428	89	1668	1532	48	22	20	1598	1601	80	63	26	9	1440	12	120	-5,0	80	334