

TECHNICAL SPECIFICATIONS

TYPE 4000

(INTERNAL TEETH)

| Drawing Nr.: | Dz (mm) | Dn (mm) | H (mm) | Lz (mm) | Ln (mm) | n | B (mm) | M (mm) | O (mm) | U (mm) | H1 (mm) | H2 (mm) | Hu (mm) | Ho (mm) | d (mm) | m (mm) | z | x.m (mm) | b (mm) | T (kg) | t (mm) | Zn (mm) | hu (mm) |
|-------------------------------|------------|-------------|-----------|-------------|------------|-----------|-----------|-----------|-----------|-------------|------------|------------|------------|------------|-----------|-----------|-----|-------------|-----------|------------|-----------|-------------|------------|
| 4002.20.20.0-0.0895.00 | 971 | 784 | 82 | 944 | 850 | 30 | 17,5 | 16 | 854 | 879 | 58 | 78 | 4 | 24 | 800 | 8 | 100 | -0,0 | 50 | 118 | 35 | 820 | 8 |
| 4004.20.20.0-0.1085.00 | 1161 | 960 | 90 | 1134 | 1040 | 36 | 17,5 | 16 | 1044 | 1069 | 66 | 78 | 12 | 24 | 980 | 10 | 98 | -0,0 | 55 | 154 | 35 | 1010 | 11 |
| 4006.20.20.0-0.1360.00 | 1440 | 1210 | 82 | 1410 | 1300 | 54 | 17,5 | 16 | 1319 | 1342 | 58 | 78 | 4 | 24 | 1220 | 10 | 122 | -5,0 | 58 | 213 | 35 | - | - |