



TECHNISCHE SPEZIFIKATIONEN TYP 4000 (AUSSENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4850.30.25.0-0.0383.00	504	300	92	436	330	16	18	16	381	384	83	83	9	9	488	8	61	0	83	64
4852.30.22.0-0.0475.00	595	382	98	540	410	24	18	16	473	477	88	88	10	10	585	5	117	0	88	85
4854.30.25.0-0.0574.00	712	470	98	640	508	24	18	16	572	576	88	88	10	10	696	8	87	0	88	123
4856.30.20.0-0.0753.00	864	678	92	800	706	36	18	16	751	755	83	83	9	9	852	6	142	0	83	114
4858.30.30.0-0.0823.00	979	718	102	893	753	36	22	20	821	825	92	92	10	10	940	10	94	0	92	197
4860.30.20.0-0.0968.00	1080	893	92	1015	922	30	18	16	966	970	83	83	9	9	1064	8	133	0	83	148
4862.30.25.0-0.1074.00	1200	976	98	1135	1012	36	20	18	1072	1076	88	88	10	10	1184	8	148	0	88	210
4864.30.30.0-0.1117.00	1289,5	985	108	1198	1035	40	22	20	1114	1120	98	98	10	10	1250	10	125	0	98	332
4866.30.30.0-0.1213.00	1380	1095	108	1290	1135	48	24	22	1210	1216	98	98	10	10	1360	10	136	0	98	325
4868.30.40.0-0.1390.00	1634	1208	148	1500	1280	48	33	30	1387	1393	138	134	10	14	1582	14	113	0	138	797