

TECHNISCHE SPEZIFIKATIONEN

TYP 5000

(AUSSENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5000.30.16.0-1.0400.00	495,5	325	55	448	352	16	13,5	12	398	402	46	46	9	9	484	4	121	+2,0	46	33
5002.30.16.0-1.0450.00	554	369	55	500	400	16	15,5	14	448	452	46	46	9	9	540	5	108	+2,5	46	41
5004.30.16.0-1.0560.00	664	479	55	610	510	20	15,5	14	558	562	46	46	9	9	650	5	130	+2,5	46	50
5006.30.16.0-1.0630.00	742,8	543	55	682	578	20	17,5	16	628	632	46	46	9	9	726	6	121	+3,0	46	61

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5016.30.20.0-1.0450.00	562,8	364	62	505	395	16	15,5	14	448	452	53	53	9	9	546	6	91	+3,0	53	49
5018.30.20.0-1.0560.00	676,8	474	62	615	505	20	15,5	14	558	562	53	53	9	9	660	6	110	+3,0	53	62
5020.30.20.0-1.0630.00	758,4	538	62	687	573	20	17,5	16	628	632	53	53	9	9	736	8	92	+4,0	53	76
5022.30.20.0-1.0710.00	838,4	618	62	767	653	24	17,5	16	708	712	53	53	9	9	816	8	102	+4,0	53	85

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5032.30.25.0-1.0764.00	892,8	662	73	830	698	24	17,5	16	762	766	64	64	9	9	876	6	146	+3,0	64	116
5034.30.25.0-1.0886.00	1030,4	784	73	952	820	30	17,5	16	884	888	64	64	9	9	1008	8	126	+4,0	64	144
5036.30.25.0-1.0980.00	1118,4	878	73	1046	914	30	17,5	16	978	982	64	64	9	9	1096	8	137	+4,0	64	155
5038.30.25.0-1.1077.00	1228	975	73	1143	1011	36	17,5	16	1075	1079	64	64	9	9	1200	10	120	+5,0	64	178

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5048.30.25.0-1.1120.00	1278	1008	73	1188	1052	36	22	20	1118	1122	64	64	9	9	1250	10	125	+5,0	64	195
5050.30.25.0-1.1180.00	1338	1068	73	1248	1112	36	22	20	1178	1182	64	64	9	9	1310	10	131	+5,0	64	206
5052.30.25.0-1.1250.00	1408	1138	73	1318	1182	40	22	20	1248	1252	64	64	9	9	1380	10	138	+5,0	64	216
5054.30.25.0-1.1320.00	1497,6	1208	73	1388	1252	42	22	20	1318	1322	64	64	9	9	1464	12	122	+6,0	64	247

TECHNISCHE SPEZIFIKATIONEN

TYP 5000

(AUSSENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5064.30.28.0-1.1400.00	1593,6	1266	80	1482	1318	36	26	24	1398	1402	71	71	9	9	1560	12	130	+6,0	71	332
5066.30.28.0-1.1500.00	1689,6	1366	80	1582	1418	40	26	24	1498	1502	71	71	9	9	1656	12	138	+6,0	71	349
5068.30.28.0-1.1600.00	1803,2	1466	80	1682	1518	40	26	24	1598	1602	71	71	9	9	1764	14	126	+7,0	71	388
5070.30.28.0-1.1700.00	1915,2	1566	80	1782	1618	44	26	24	1698	1702	71	71	9	9	1876	14	134	+7,0	71	431

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5080.30.36.0-1.1700.00	1943,2	1529	100	1805	1595	32	33	30	1698	1702	90	90	10	10	1904	14	136	+7,0	90	653
5082.30.36.0-1.1800.00	2041,2	1629	100	1905	1695	36	33	30	1798	1802	90	90	10	10	2002	14	143	+7,0	90	685
5084.30.36.0-1.1900.00	2139,2	1729	100	2005	1795	36	33	30	1898	1902	90	90	10	10	2100	14	150	+7,0	90	721
5086.30.36.0-1.2000.00	2237,2	1829	100	2105	1895	40	33	30	1998	2002	90	90	10	10	2198	14	157	+7,0	90	749

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5096.30.40.0-1.2000.00	2252,8	1824	108	2110	1890	42	33	30	1997	2003	98	98	10	10	2208	16	138	+8,0	98	848
5098.30.40.0-1.2128.00	2380,8	1952	108	2238	2018	48	33	30	2125	2131	98	98	10	10	2336	16	146	+8,0	98	896
5100.30.40.0-1.2240.00	2492,8	2064	108	2350	2130	48	33	30	2237	2243	98	98	10	10	2448	16	153	+8,0	98	946
5102.30.40.0-1.2368.00	2620,8	2192	108	2478	2258	56	33	30	2365	2371	98	98	10	10	2576	16	161	+8,0	98	993

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5112.30.45.0-1.2240.00	2516,4	2057	119	2357	2123	48	33	30	2237	2243	109	109	10	10	2466	18	137	+9,0	109	1122
5114.30.45.0-1.2366.00	2642,4	2183	119	2483	2249	52	33	30	2363	2369	109	109	10	10	2592	18	144	+9,0	109	1182
5116.30.45.0-1.2510.00	2786,4	2327	119	2627	2382	56	33	30	2507	2513	109	109	10	10	2736	18	152	+9,0	109	1258
5118.30.45.0-1.2654.00	2930,4	2471	119	2771	2537	60	33	30	2651	2657	109	109	10	10	2880	18	160	+9,0	109	1329

TECHNISCHE SPEZIFIKATIONEN

TYP 5000

(AUSSENVERZÄHNUNG)

Drawing Nr.:	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
5128.30.50.0-1.2500.00	2796	2309	130	2625	2375	60	33	30	2497	2503	120	120	10	10	2740	20	137	+10,0	120	1453
5130.30.50.0-1.2660.00	2956	2469	130	2785	2535	64	33	30	2657	2663	120	120	10	10	2900	20	145	+10,0	120	1544
5132.30.50.0-1.2800.00	3096	2609	130	2925	2675	72	33	30	2797	2803	120	120	10	10	3040	20	152	+10,0	120	1616
5134.30.50.0-1.3000.00	3296	2809	130	3125	2875	76	33	30	2997	3003	120	120	10	10	3240	20	162	+10,0	120	1733